




tandwielen, rechte vertanding, materiaal C43
 pignons droits, matériau C43
 module **4.0** (b = 40 mm)



Z*	Da	d	dn	db	b	l	Kg
12	56	48	35	14	40	60	0,63
13	60	52	40	14	40	60	0,78
14	64	56	45	14	40	60	0,93
15	68	60	45	14	40	60	1,05
16	72	64	50	16	40	60	1,20
17	76	68	50	16	40	60	1,33
18	80	72	50	16	40	60	1,47
19	84	76	60	16	40	60	1,75
20	88	80	60	16	40	60	1,90
21	92	84	70	16	40	60	2,22
22	96	88	70	16	40	60	2,39
23	100	92	75	20	40	60	2,60
24	104	96	75	20	40	60	2,79
25	108	100	75	20	40	60	2,98
26	112	104	75	20	40	60	3,18
27	116	108	75	20	40	60	3,39
28	120	112	75	20	40	60	3,60
29	124	116	75	20	40	60	3,83
30	128	120	75	20	40	60	4,06
31	132	124	80	20	40	60	4,69
32	136	128	80	20	40	60	4,64
33	140	132	80	20	40	60	4,90
34	144	136	80	20	40	60	5,16
35	148	140	80	20	40	60	5,43
36	152	144	80	25	40	60	5,63
37	-	-	-	-	-	-	-
38	160	152	-	25	40	-	5,20
39	-	-	-	-	-	-	-
40	168	160	-	25	40	-	6,11
41	-	-	-	-	-	-	-
42	-	-	-	-	-	-	-
43	-	-	-	-	-	-	-
44	-	-	-	-	-	-	-
45	188	180	-	25	40	-	7,78
46	-	-	-	-	-	-	-
47	-	-	-	-	-	-	-
48	200	192	-	25	40	-	8,87

Z*	Da	d	dn	db	b	l	Kg
49	-	-	-	-	-	-	-
50	208	200	-	25	40	-	9,65
51	-	-	-	-	-	-	-
52	216	208	-	25	40	-	10,45
53	-	-	-	-	-	-	-
54	-	-	-	-	-	-	-
55	228	220	-	25	40	-	11,71
56	-	-	-	-	-	-	-
57	236	228	-	25	40	-	12,59
58	-	-	-	-	-	-	-
59	-	-	-	-	-	-	-
60	248	240	-	25	40	-	13,97
61	-	-	-	-	-	-	-
62	-	-	-	-	-	-	-
63	-	-	-	-	-	-	-
64	-	-	-	-	-	-	-
65	268	260	-	25	40	-	16,43
66	-	-	-	-	-	-	-
67	-	-	-	-	-	-	-
68	-	-	-	-	-	-	-
69	-	-	-	-	-	-	-
70	288	280	-	25	40	-	19,09
72	-	-	-	-	-	-	-
75	308	300	-	25	40	-	21,94
76	312	304	-	30	40	-	22,47
80	328	320	-	30	40	-	24,93
85	348	340	-	30	40	-	28,18
90	368	360	-	30	40	-	31,62
95	388	380	-	30	40	-	35,26
100	408	400	-	30	40	-	39,11
110	448	440	-	30	40	-	47,38
114	464	456	-	30	40	-	50,91
120	-	-	-	-	-	-	-
127	-	-	-	-	-	-	-

materiaal / matériau: C43 UNI 7847

ingrijphoek / angle d'attaque: 20°

Z*: aantal tanden / nombre de dents