




tandwielen, rechte vertanding, materiaal C43  
 pignons droits, matériau C43  
 module **5.0** (b = 50 mm)



© Aandrijvingen Gallon NV 100510

Z*	Da	d	dn	db	b	l	Kg
12	70	60	45	20	50	75	1,21
13	75	65	50	20	50	75	1,47
14	80	70	55	20	50	75	1,76
15	85	75	60	20	50	75	2,07
16	90	80	65	20	50	75	2,40
17	95	85	70	20	50	75	2,75
18	100	90	70	20	50	75	3,02
19	105	95	70	20	50	75	3,30
20	110	100	80	20	50	75	3,83
21	115	105	80	20	50	75	4,15
22	120	110	80	20	50	75	4,48
23	125	115	90	20	50	75	5,08
24	130	120	90	20	50	75	5,44
25	135	125	90	20	50	75	5,82
26	140	130	100	20	50	75	6,50
27	145	135	100	20	50	75	6,91
28	150	140	100	25	50	75	7,22
29	155	145	110	25	50	75	7,98
30	160	150	110	25	50	75	8,44
31	-	-	-	-	-	-	-
32	170	160	-	25	50	-	7,62
33	-	-	-	-	-	-	-
34	-	-	-	-	-	-	-
35	185	175	-	25	50	-	9,16
36	-	-	-	-	-	-	-
37	-	-	-	-	-	-	-
38	200	190	-	25	50	-	10,84
39	-	-	-	-	-	-	-
40	210	200	-	25	50	-	12,04
41	-	-	-	-	-	-	-
42	-	-	-	-	-	-	-
43	-	-	-	-	-	-	-
44	-	-	-	-	-	-	-
45	235	225	-	25	50	-	15,30
46	-	-	-	-	-	-	-
47	-	-	-	-	-	-	-
48	250	240	-	25	50	-	17,44

Z*	Da	d	dn	db	b	l	Kg
49	-	-	-	-	-	-	-
50	260	250	-	30	50	-	18,86
51	-	-	-	-	-	-	-
52	270	260	-	30	50	-	20,43
53	-	-	-	-	-	-	-
54	-	-	-	-	-	-	-
55	285	275	-	30	50	-	22,89
56	-	-	-	-	-	-	-
57	295	285	-	30	50	-	24,62
58	-	-	-	-	-	-	-
59	-	-	-	-	-	-	-
60	310	300	-	30	50	-	27,31
61	-	-	-	-	-	-	-
62	-	-	-	-	-	-	-
63	-	-	-	-	-	-	-
64	-	-	-	-	-	-	-
65	335	325	-	30	50	-	32,12
66	-	-	-	-	-	-	-
67	-	-	-	-	-	-	-
68	-	-	-	-	-	-	-
69	-	-	-	-	-	-	-
70	360	350	-	30	50	-	37,31
72	-	-	-	-	-	-	-
75	385	375	-	30	50	-	42,88
76	390	380	-	30	50	-	44,04
80	410	400	-	30	50	-	48,84
85	435	425	-	30	50	-	55,19
90	460	450	-	30	50	-	61,92
95	485	475	-	30	50	-	69,03
100	510	500	-	30	50	-	76,53
110	560	550	-	30	50	-	92,69
114	580	570	-	30	50	-	99,59
120	-	-	-	-	-	-	-
127	-	-	-	-	-	-	-

materiaal / matériau: C43 UNI 7847

ingrijphoek / angle d'attaque: 20°

Z\*: aantal tanden / nombre de dents