



conische tandwielen met spiraalvertanding

pignons coniques spiroïdaux

staal / acier: (C43)

1 : 1



03

© Aandrijvingen Gallon NV 100510

module	Z*	De	Dp	A	F	Dn	D1	dm	L	Lm	Kg
2,0	16	34,6	32,0	19,9	9	25	10	29	16,9	9,5	0,06
	20	42,6	40,0	24,9	12	32	10	36	21,7	12,0	0,14
	25	52,6	50,0	27,4	14	40	12	42	24,8	12,0	0,25
	30	62,6	60,0	29,9	16	50	12	48	26,9	13,0	0,42
2,5	16	43,2	40,0	24,8	10	32	12	37	21,8	13,0	0,13
	20	53,3	50,0	30,2	12	40	12	46	26,7	16,0	0,27
	25	65,8	62,5	33,2	15	50	15	53	29,9	16,0	0,47
	30	78,3	75,0	35,0	18	55	15	59	31,8	16,0	0,69
3,0	16	51,9	48,0	29,4	12	40	15	44	25,8	16,0	0,23
	20	63,9	60,0	34,5	18	45	15	51	30,7	13,5	0,41
	25	78,9	75,0	37,5	20	55	15	60	33,7	16,0	0,72
	30	93,9	90,0	39,5	22	60	20	68	35,8	19,0	0,99
3,5	16	60,2	56,0	34,1	14	45	15	51	29,5	17,5	0,36
	20	74,2	70,0	35,9	15	55	15	59	31,2	19,0	0,62
	25	91,7	87,5	40,5	21	65	20	68	36,5	18,0	1,11
	30	109,2	105,0	41,9	24	70	20	76	37,0	17,0	1,64
4,0	16	68,8	64,0	36,0	15	50	15	56	30,8	17,0	0,51
	20	84,8	80,0	37,5	17	60	18	64	32,5	18,0	0,81
	25	104,8	100,0	40,4	21	70	20	74	35,2	18,0	1,33
	30	124,8	120,0	43,2	25	80	25	84	38,1	16,0	2,10
4,5	16	77,4	72,0	39,3	15	55	18	63	33,5	18,5	0,67
	20	95,4	90,0	42,8	20	65	20	72	36,5	18,0	1,14
	25	117,9	112,5	45,0	25	75	20	82	39,0	18,0	1,87
	30	140,4	135,0	48,0	28	90	25	94	42,0	17,0	2,98
5,0	16	86,0	80,0	41,9	17	60	20	68	35,5	18,0	0,88
	20	106,0	100,0	44,7	21	70	20	78	37,7	18,5	1,47
	25	131,0	125,0	47,8	26	90	20	90	41,8	18,5	2,67
	30	156,0	150,0	52,5	32	110	30	103	45,7	18,0	4,25

onder hoek van / angle des axes: 90°

drukhoek / angle d'attaque: 20°

Z*: aantal tanden / nombre de dents