

holle worm
 axe creux
 asafstand / distance entraxe
80 mm



holle worm axe-creux	DIN 3975/3976
rechtsgangige vertanding <i>denture à droite</i>	
staal <i>acier</i>	1.0503 (C45)

04

i	module	z ₁	d _m	d _a	d _n	d _b	b	t ₂	l ₁	l ₂	b ₁	Kg	bestel nr. n° de comm.
7,5:1	4,00	4	40,0	48,0	30,0	20	6	2,8	29,0	39,0	50	0,429	173-540-440
10,0:1	3,15	4	33,5	39,8	25,0	16	5	2,3	26,0	36,0	46	0,280	173-531-433
12,5:1	2,50	4	33,5	38,5	27,0	18	6	2,8	25,5	37,5	46	0,266	173-525-433
15,0:1	4,00	2	40,0	48,0	30,0	20	6	2,8	29,0	39,0	50	0,429	173-540-240
20,0:1	3,15	2	33,5	39,8	25,0	16	5	2,3	26,0	36,0	46	0,280	173-531-233
25,0:1	2,50	2	33,5	38,5	27,0	18	6	2,8	25,5	37,5	46	0,266	173-525-233
30,0:1	4,00	1	40,0	48,0	30,0	20	6	2,8	29,0	39,0	50	0,429	173-540-140
40,0:1	3,15	1	33,5	39,8	25,0	16	5	2,3	26,0	36,0	46	0,280	173-531-133
50,0:1	2,50	1	33,5	38,5	27,0	18	6	2,8	25,5	37,5	46	0,266	173-525-133
62,0:1	2,00	1	35,5	39,5	30,0	20	6	2,8	21,5	33,5	38	0,249	173-520-135
82,0:1	1,60	1	28,0	31,2	23,5	16	5	2,3	20,0	30,0	36	0,143	173-516-128

© Aandrijvingen Gallon NV 100510



z	aantal tanden / nombre de dents
z ₁	aantal gangen / nombre d'entrées
d _x **	ca. ø staal / brons ca. ø acier / bronze
i	verhouding <i>rapport</i>