

holle worm
 axe creux
 asafstand / distance entraxe
100 mm



holle worm axe-creux	DIN 3975/3976
rechtsgangige vertanding <i>denture à droite</i>	
staal <i>acier</i>	1.0503 (C45)

04

i	module	z_1	d_m	d_a	d_n	d_b	b	t_2	l_1	l_2	b_1	Kg	bestel nr. n° de comm.
7,5:1	5,00	4	50,0	60,0	37,5	26	8	3,3	35,0	50,0	60	0,776	173-650-450
10,0:1	4,00	4	40,0	48,0	30,0	20	6	2,8	31,0	42,0	54	0,451	173-640-440
12,5:1	3,15	4	42,5	48,8	34,5	24	8	3,3	28,0	44,0	50	0,450	173-631-442
15,0:1	5,00	2	50,0	60,0	37,5	26	8	3,3	35,0	50,0	60	0,776	173-650-250
20,0:1	4,00	2	40,0	48,0	30,0	20	6	2,8	31,0	42,0	54	0,451	173-640-240
25,0:1	3,15	2	42,5	48,8	34,5	24	8	3,3	28,0	44,0	50	0,450	173-631-242
30,0:1	5,00	1	50,0	60,0	37,5	26	8	3,3	35,0	50,0	60	0,776	173-650-150
40,0:1	4,00	1	40,0	48,0	30,0	20	6	2,8	31,0	42,0	54	0,451	173-640-140
50,0:1	3,15	1	42,5	48,8	34,5	24	8	3,3	28,0	44,0	50	0,450	173-631-142
63,0:1	2,50	1	42,5	47,5	35,5	26	8	3,3	25,0	41,0	45	0,385	173-625-142
82,0:1	2,00	1	35,5	39,5	30,0	20	6	2,8	23,5	35,5	42	0,270	173-620-135

© Aandrijvingen Gallon NV 100510



z	aantal tanden / nombre de dents
z_1	aantal gangen / nombre d'entrées
d_x^{**}	ca. ø staal / brons ca. ø acier / bronze
i	verhouding rapport