

holle worm  
 axe creux  
 asafstand / distance entraxe  
**125 mm**



<b>holle worm axe-creux</b>	<b>DIN 3975/3976</b>
rechtsgangige vertanding <i>denture à droite</i>	
staal <i>acier</i>	1.0503 (C45)

i	module	z <sub>1</sub>	d <sub>m</sub>	d <sub>a</sub>	d <sub>n</sub>	d <sub>b</sub>	b	t <sub>2</sub>	l <sub>1</sub>	l <sub>2</sub>	b <sub>1</sub>	Kg	bestel nr. n° de comm.
7,25:1	6,30	4	63,0	75,6	47	32	10	3,3	49,0	68,0	86	1,780	<b>173-763-463</b>
10,00:1	5,00	4	50,0	60,0	37	26	8	3,3	39,5	54,5	69	0,882	<b>173-750-450</b>
12,50:1	4,00	4	50,0	58,0	40	30	8	3,3	34,0	50,0	60	0,675	<b>173-740-450</b>
14,50:1	6,30	2	63,0	75,6	47	32	10	3,3	49,0	68,0	86	1,780	<b>173-763-263</b>
20,00:1	5,00	2	50,0	60,0	37	26	8	3,3	39,5	54,5	69	0,882	<b>173-750-250</b>
25,00:1	4,00	2	50,0	58,0	40	30	8	3,3	34,0	50,0	60	0,675	<b>173-740-250</b>
29,00:1	6,30	1	63,0	75,6	47	32	10	3,3	49,0	68,0	86	1,780	<b>173-763-163</b>
40,00:1	5,00	1	50,0	60,0	37	26	8	3,3	39,5	54,5	69	0,882	<b>173-750-150</b>
50,00:1	4,00	1	50,0	58,0	40	30	8	3,3	34,0	50,0	60	0,675	<b>173-740-150</b>
62,00:1	3,15	1	53,0	59,3	45	32	10	3,3	33,0	53,0	60	0,813	<b>173-731-153</b>
83,00:1	2,50	1	42,5	47,5	36	26	8	3,3	27,5	43,5	50	0,419	<b>173-725-142</b>

© Aandrijvingen Gallon NV 100510



z	aantal tanden / nombre de dents
z <sub>1</sub>	aantal gangen / nombre d'entrées
d <sub>x</sub> **	ca. ø staal / brons ca. ø acier / bronze
i	verhouding rapport