



DIN ISO	steek x inwendige breedte pas x largeur intérieure	steek pas	gewicht poids	binnenschakel maillon intérieur		buitenschakel maillon ext.				
				plaatdikte largeur		F	D	E	A	C
		p	Kg/m.	B	G					
04 BSS	6 x 2,8 mm	6,000	0,11	2,80	0,60	5,00	6,80	7,80	4,00	1,85
05 BSS	8 x 3,0 mm	8,000	0,20	3,00	0,80	7,10	8,20	8,90	5,00	2,31
06 BSS	3/8 x 5/32"	9,525	0,41	5,72	1,30	8,20	13,15	14,10	6,35	3,28
08 BSS	1/2 x 5/16"	12,700	0,70	7,75	1,60	11,80	16,70	18,20	8,51	4,45
10 BSS	5/8 x 3/8"	18,875	0,94	9,65	1,70	14,70	19,50	20,90	10,16	5,08
12 BSS	3/4 x 7/16"	19,050	1,16	11,68	1,85	16,00	22,50	24,20	12,07	5,72
16 BSS	1" x 17 mm	25,400	2,73	17,02	4,15/3,1	21,00	36,10	37,40	15,88	8,28
20 BSS	1 1/4 x 3/4"	31,750	3,73	19,56	4,1/3,5	26,40	41,30	45,00	19,05	10,19

alle afmetingen in mm / toutes les dimensions en mm

onderdelen en sloten / pièces détachées et raccords

3



sluitschakel met veer
maillon raccord droit
à agrafe

6



verloopschakel
met splitpen
maillon coudé simple
à goupilles