




tandriemschijven voor klembussen H
poulies dentées à moyeu amovible type H
H 200 stap / pas 1/2" (12,7 mm)
50,8 mm riembreedte / largeur



16F



17F



20

code	type	Z*	klembus moyeu	max. boring alésage max.	dp	de	Df	Dm	Di	F	L	R	flens nr. n° de flasque	Kg
TL 18 H 200	16F	18	1210	32	72,77	71,39	79	-	52	58,0	25,0	33,0	313	0,84
TL 19 H 200	16F	19	1210	32	76,81	75,44	83	-	56	58,0	25,0	33,0	314	0,96
TL 20 H 200	16F	20	1610	42	80,85	79,48	87	-	60	58,0	25,0	33,0	315	0,93
TL 21 H 200	16F	21	1610	42	84,89	83,52	91	-	64	58,0	25,0	33,0	316	1,07
TL 22 H 200	16F	22	1610	42	88,94	87,56	93	-	67	58,0	25,0	33,0	317	1,25
TL 23 H 200	16F	23	1610	42	92,98	91,61	97	-	70	58,0	25,0	33,0	318	1,40
TL 24 H 200	16F	24	1610	42	97,02	95,65	103	-	73,5	58,0	25,0	33,0	320	1,55
TL 25 H 200	16F	25	1610	42	101,06	99,69	106	-	77	58,0	25,0	33,0	321	1,71
TL 26 H 200	16F	26	1610	42	105,11	103,73	111	-	82	58,0	25,0	33,0	322	1,84
TL 27 H 200	16F	27	1610	42	109,15	107,78	115	-	85	58,0	25,0	33,0	323	2,06
TL 28 H 200	16F	28	1610	42	113,19	111,82	119	-	90,5	58,0	25,0	33,0	325	2,17
TL 30 H 200	16F	30	1610	42	121,28	119,90	127	-	98	58,0	25,0	33,0	327	2,60
TL 32 H 200	16F	32	2012	50	129,36	127,99	135	-	106	58,0	32,0	26,0	328	2,95
TL 36 H 200	17F	36	2012	50	145,53	144,16	152	102	121	58,0	32,0	26,0	334	3,62
TL 40 H 200	17F	40	2012	50	161,70	160,33	168	106	138	58,0	32,0	26,0	338	4,33
TL 44 H 200	17F	44	2012	50	177,87	176,50	184	106	152	58,0	32,0	26,0	339	5,33
TL 48 H 200	17F	48	2517	60	194,04	192,67	200	119	169	58,0	45,0	13,0	342	6,47

materiaal: staal / matériau: acier

TL 60 H 200	20	60	2517	60	242,55	241,18	-	119	223	60,0	45,0	7,5	-	5,86
TL 72 H 200	20	72	2517	60	291,06	289,69	-	119	270	60,0	45,0	7,5	-	7,42
TL 84 H 200	20	84	2517	60	339,57	338,20	-	119	320	60,0	45,0	7,5	-	8,73
TL 96 H 200	20	96	2517	60	388,08	386,71	-	119	366	60,0	45,0	7,5	-	10,83
TL120H 200	20	120	2517	60	485,10	483,73	-	119	462	60,0	45,0	7,5	-	14,95

materiaal: gietijzer / matériau: fonte

Z*: aantal tanden / nombre de dents