





tandriemschijven voor klembussen 8M
poulies dentées à moyeu amovible type 8M
8M 20 stap / pas 8 mm
20 mm riembreedte / largeur



code	type	Z*	klembus moyeu	max. boring alésage max.	dp	de	Df	Dm	Di	F	L	R	flens nr. n° de flasque	Kg
TL 22-8M-20	16F	22	1008	25	56,02	54,65	60	-	37	28	22	6	308	0,25
TL 24-8M-20	16F	24	1108	25	61,11	59,74	66	-	44	28	22	6	310	0,30
TL 26-8M-20	16F	26	1108	25	66,21	64,84	71	-	45	28	22	6	311	0,36
TL 28-8M-20	16F	28	1108	25	71,30	70,08	75	-	50	28	22	6	312	0,45
TL 30-8M-20	16F	30	1108	25	76,39	75,13	83	-	58	28	22	6	314	0,55
TL 32-8M-20	16F	32	1610	42	81,49	80,16	87	-	63	28	25	3	315	0,43
TL 34-8M-20	16F	34	1610	42	86,58	85,21	91	-	64	28	25	3	316	0,57
TL 36-8M-20	16F	36	1610	42	91,67	90,30	98	-	68	28	25	3	319	0,70
TL 38-8M-20	16F	38	1610	42	96,77	95,39	103	-	72	28	25	3	320	0,82
TL 40-8M-20	16F	40	1610	42	101,86	100,49	106	-	76	28	25	3	321	1,10
TL 44-8M-20	10F	44	2012	50	112,05	110,67	119	92	-	28	32	4	325	1,20
TL 48-8M-20	10F	48	2012	50	122,23	120,86	127	96	-	28	32	4	327	1,65
TL 56-8M-20	10F	56	2012	50	142,60	141,23	148	110	-	28	32	4	333	2,50
TL 64-8M-20	11F	64	2012	50	162,97	161,60	168	110	137	28	32	4	338	2,60
TL 72-8M-20	11F	72	2012	50	183,35	181,97	192	110	158	28	32	4	340	3,40

materiaal: staal / matériau: acier

TL 80-8M-20	11	80	2012	50	203,72	202,35	-	110	180	28	32	4	-	3,60
TL 90-8M-20	11	90	2012	50	229,18	227,81	-	110	204	28	32	4	-	4,10

materiaal: gietijzer / matériau: fonte

Z*: aantal tanden / nombre de dents