



tandriemschijven 5M
poulies dentées type 5M
5M 25 stap / *pas* 5 mm
25 mm riembreedte / *largeur*



09

code	type	Z*	dp	de	Df	Dm	Di	F	L	d	flens nr. n° de flasque	Kg
12-5M-25	2F	12	19,10	17,96	23	12,5	-	30,5	36,0	6	202	0,05
14-5M-25	2F	14	22,28	21,14	25	13,5	-	30,5	36,0	6	203	0,08
15-5M-25	2F	15	23,87	22,73	28	16,0	-	30,5	36,0	6	204	0,09
16-5M-25	2F	16	25,46	24,32	28	16,5	-	30,5	36,0	6	204	0,11
18-5M-25	2F	18	28,65	27,51	32	20,0	-	30,5	36,0	6	205	0,13
20-5M-25	2F	20	31,83	30,69	36	23,0	-	30,5	36,0	6	206	0,17
21-5M-25	2F	21	33,42	32,28	38	24,0	-	30,5	38,0	6	207	0,20
22-5M-25	2F	22	35,01	33,87	38	25,5	-	30,5	38,0	6	207	0,22
24-5M-25	2F	24	38,20	37,06	42	27,0	-	30,5	38,0	6	208	0,26
26-5M-25	2F	26	41,38	40,24	44	30,0	-	30,5	38,0	6	209	0,32
28-5M-25	2F	28	44,56	43,42	48	30,5	-	30,5	38,0	6	210	0,37
30-5M-25	2F	30	47,75	46,60	51	35,0	-	30,5	38,0	6	211	0,44
32-5M-25	2F	32	50,93	49,79	54	38,0	-	30,5	38,0	8	212	0,48
36-5M-25	2F	36	57,30	56,16	60	38,0	-	30,5	38,0	8	214	0,59
40-5M-25	2F	40	63,66	62,52	71	38,0	-	30,5	38,0	8	217	0,75

materiaal: staal / *matériau: acier*

44-5M-25	2	44	70,03	68,89	-	38,0	-	30,5	40,0	8	-	0,32
48-5M-25	2	48	76,39	75,25	-	38,0	-	30,5	40,0	8	-	0,28
60-5M-25	2	60	95,49	94,35	-	50,0	-	30,5	40,0	8	-	0,44
72-5M-25	2	72	114,59	113,45	-	50,0	-	30,5	40,0	8	-	0,85

materiaal: aluminium UNI 9006 - T6 / *matériau: aluminium UNI 9006 - T6*

Z*: aantal tanden / *nombre de dents*

© Aandrijvingen Gallon NV 100510