



tandriemschijven AT 5  
 poulies dentées type AT 5  
**AT 5** stap / pas 5 mm  
**25 mm** riembreedte / largeur



09

code	type	Z*	de	Df	Dm	F	L	d	flens nr. n° de flasque	Kg
36 BAT 5 12	2F	12	17,85	23	10	30	36	-	201	0,03
36 BAT 5 14	2F	14	21,05	25	13	30	36	-	203	0,04
36 BAT 5 15	2F	15	22,65	28	16	30	36	-	204	0,04
36 BAT 5 16	2F	16	24,20	32	18	30	36	-	205	0,05
36 BAT 5 18	2F	18	27,40	32	20	30	36	-	205	0,06
36 BAT 5 19	2F	19	29,00	36	22	30	36	-	206	0,07
36 BAT 5 20	2F	20	30,60	36	23	30	36	-	206	0,08
36 BAT 5 22	2F	22	33,85	38	24	30	36	-	207	0,08
36 BAT 5 24	2F	24	37,00	42	26	30	36	8	208	0,11
36 BAT 5 25	2F	25	38,55	44	26	30	36	8	209	0,12
36 BAT 5 26	2F	26	40,20	44	26	30	36	8	209	0,12
36 BAT 5 27	2F	27	41,80	48	30	30	36	8	210	0,13
36 BAT 5 28	2F	28	43,35	48	32	30	36	8	210	0,14
36 BAT 5 30	2F	30	46,55	51	34	30	36	8	211	0,15
36 BAT 5 32	2F	32	49,70	54	38	30	36	8	212	0,18
36 BAT 5 36	2F	36	56,05	63	38	30	36	8	215	0,23
36 BAT 5 40	2F	40	62,45	66	40	30	36	8	216	0,28
36 BAT 5 42	2F	42	65,60	71	40	30	36	8	217	0,29
36 BAT 5 44	2	44	68,80	-	45	30	36	8	-	0,31
36 BAT 5 48	2	48	75,15	-	50	30	36	8	-	0,40
36 BAT 5 60	2	60	94,25	-	65	30	36	8	-	0,61

materiaal: aluminium UNI 9006 - T6 / matériau: aluminium UNI 9006 - T6

Z\*: aantal tanden / nombre de dents