


hoekkasten, versterkte uitvoering
renvois d'angle, exécution renforcé
 vermogenstabel / *table de puissance*
 assen / *arbres* - **12mm -> 19mm**



assen van 12 mm
arbres de 12 mm

rpm	reductie / réduction 1 : 1		reductie / réduction 1 : 2		reductie / réduction 1 : 3		reductie / réduction 1 : 4		reductie / réduction 1 : 5	
	kW	Nm	kW	Nm	kW	Nm	kW	Nm	kW	Nm
2800	3.08	10.1	1.61	10.6	0.59	5.8				
2000	2.30	10.6	1.19	10.9	0.46	6.3				
1500	1.88	11.5	0.94	11.5	0.38	6.9				
1000	1.36	12.5	0.68	12.5	0.27	7.5				
800	1.17	13.4	0.59	13.4	0.23	8.1				
600	0.94	14.4	0.47	14.4	0.19	8.6				
400	0.67	15.4	0.34	15.4	0.13	8.9				
100	0.18	16.8	0.09	16.7	0.03	9.4				
50	0.10	18.2	0.05	18.2	0.02	9.8				
10	0.02	19.2	0.01	19.2	0.01	10.1				

assen van 19 mm
arbres de 19 mm

rpm	reductie / réduction 1 : 1		reductie / réduction 1 : 2		reductie / réduction 1 : 3		reductie / réduction 1 : 4		reductie / réduction 1 : 5	
	kW	Nm	kW	Nm	kW	Nm	kW	Nm	kW	Nm
2800	16.27	53.3	6.51	42.6	2.40	23.6	2.70	27.1	1.32	21.6
2000	11.94	54.7	4.73	43.4	1.75	24.0	1.50	27.5	0.96	21.9
1500	9.17	56.1	3.60	44.0	1.34	24.5	1.13	27.6	0.72	22.1
1000	6.26	57.4	2.46	45.1	0.91	24.9	0.77	28.3	0.49	22.5
800	5.07	58.1	1.99	45.7	0.73	25.1	0.62	28.5	0.39	22.6
600	3.85	58.8	1.51	46.1	0.55	25.4	0.47	28.8	0.30	22.8
400	2.62	60.0	1.02	46.7	0.37	25.8	0.32	29.0	0.20	22.9
100	0.69	62.9	0.27	48.8	0.10	26.4	0.08	29.7	0.05	23.4
50	0.35	63.7	0.13	49.3	0.05	26.6	0.04	29.9	0.03	23.6
10	0.07	64.6	0.03	49.7	0.01	26.8	0.01	30.2	0.01	23.8

© Aandrijvingen Gallon NV 100510